

SPECIFICATION OF VARIOUS ITEMSLaptop (Laptop)

Description	
Processor	4MB Cache, up to 4.1 GHz Intel core i3-10110U (quote separate price)4GB 6MB Cache, up to 3.6 GHz Intel core i5-1035G1 (quote separate price)8GB DDR4
Ram	Minimum 4 GB or More
Graphics	2 GB or more
Memory	Minimum 1 TB HDD or more
OS	Preloaded Licensed Version of Window 10 or more
Display	15.6" HD LED
Others	LAN,WI-FI,Bluetooth,integrated web cam,key board with palm rest,4 usb port,HDMI port,VGA port card reader,DVD RW
Warranty	Onsite 3 year

2. Laser Printer

Description	
Processor	266 Mhz
Print Speed	Up to 18 PPM
Print Quality	Upto 600 X 600 X 2 dpi(1200 dpi effective output
Print Technology	Laser
Compatible OS	Window 7 or greater version of window
Duplex Printing	Yes
Paper Handling	150 sheet input tray ,100 sheet output bin.
Warranty	onsite

3. UPS

Description	
Type	1000VA & 600 VA(quotes separate Price )
Input	120 V to 260V
Output	Pf-0.6
Battery Make	Exide, Panasonic, Amar Raja,HBL Nife, sunshine, Global Yuasa, Prostar M, Amco
Back up	Minimum 30 minutes on full load
Wave Form	with necessary cable and plug
Cable	Pure sine wave out put on battery mode,220/-7%

4. Scanner

Description	
Type	Flat Bed
Document feeding	manual sheet feeding
Digital sending feature	Scan, Copy, scan to application or more like scan to email, scan to pdf.
Scanning Mode	Black and white, 256 level gray Scale,24-bit colour
Scanning Resolution	100*100 dpi,150*150 dpi,200*200 dpi,240 *240 dpi,300*300 dpi,400*400 dpi,600*600 dpi or more
Scanning Speed	<b>black &amp; White</b> -04 ppm(simplex)or higher <b>256 level gray scale</b> -03 ppm (simplex)or higher <b>24-bit colour</b> -02 ppm9Simplex)

11/02/2020

**05. All in one Printer/Scanner/Copier (inkjet)**

<b>PRINT</b>		
<b>Maximum Printing Resolution</b>	4800 (horizontal) <sup>*1</sup> x 1200 (vertical) dpi	
<b>Print Head / Ink</b>	Type:	INK Tank
<b>Print Speed<sup>*2</sup></b>	Document: Col	ESAT / Simplex: approx. 4.0ipm
	Document: B / W	ESAT / Simplex: approx. 7.7ipm
	Photo (4 x 6")	PP-201 / Borderless: approx. 65secs.
<b>Printable Width</b>	Up to 203.2mm (8in.)	
<b>Printable Area</b>	Borderless Printing <sup>*3</sup>	Top / Bottom / Right / Left margin: each 0mm [Supported Paper Size: 4 x 6", 5 x 7", Square (5 x 5")]
	Bordered Printing	Top margin: 3mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (LTR / LGL: Left: 6.4mm, Right: 6.3mm)
<b>Recommended Printing Area</b>	Top margin: 31.6mm Bottom margin: 29.2mm	
<b>Paper Size</b>	A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", Square (5 x 5"), Custom size (width 101.6 - 215.9mm, length 127 - 676mm)	
<b>Paper Handling Rear Tray (Maximum Number)</b>	Plain Paper	A4, A5, B5, LTR = 60, LGL = 10
	Photo Paper Plus Glossy II (PP-201)	4 x 6" = 20, Square (5 x 5") = 10
	Glossy Photo Paper "Everyday Use" (GP-508)	4 x 6" = 20
	Photo Paper Plus Glossy II (PP-208)	4 x 6" = 20
	Photo Stickers, Free Cutting (PS-208)	4 x 6" = 1
	Removable Photo Sticker, Free Cutting (PS-308R)	4 x 6" = 1
	Rear Tray	Plain Paper: 64 - 105g/m <sup>2</sup> ,
<b>Ink End Sensor</b>	Dot count	
<b>Print Head Alignment</b>	Manual	
<b>SCANNER</b>		
<b>Scanner Type</b>	Flatbed	
<b>Scanning Method</b>	Contact Image Sensor (CIS)	
<b>Optical Resolution</b>	600 x 1200dpi	
<b>Scanning Bit Depth (Input/Output)</b>	Grayscale	16 / 8-bit
	Colour	RGB each 16 / 8-bit
<b>Line Scanning Speed</b>	Grayscale	1.5ms/line (300dpi)
	Colour	3.5ms/line (300dpi)
<b>Scanning Speed</b>	Reflective	A4 Colour / 300dpi: Approx. 14sec.
<b>Maximum Document Size</b>	Flatbed	A4 / LTR (216 x 297mm)
<b>COPY</b>		
<b>Maximum Document Size</b>	A4 / LTR (216 x 297mm)	
<b>Compatible Media</b>	Size	A4 / A5 / B5 / LTR / 4 x 6" / 5 x 7" / Square (5 x 5")
	Type	Plain Paper

*Handwritten signature*

	Photo Paper Plus Glossy II (PP-201) Glossy Photo Paper "Everyday Use" (GP-508) Photo Paper Plus Glossy II (PP-208)	
Image Quality	2 Positions (Draft, Standard)	
Copy Speed	Document: Colour	sFCOT / Simplex: Approx. 27sec. sESAT / Simplex: Approx. 3.0ipm
Multiple Copy	Black / Colour	1 - 20 pages
Warranty	Onsite	

#### 06. All in one Printer/Scanner/Copier (Laser)

<b>PRINT</b>		
Printing Method	Monochrome Laser Beam Printing	
Print Speed (A4)	23ppm	
Print Resolution	600 x 600dpi	
Print Quality with Image Refinement Technology	1,200 x 1,200dpi (equivalent)	
Warm-Up Time (From Power On)	13.5secs. or less	
First Print Out Time (FPOT) A4	Approx. 6.0secs.	
Recovery Time (From Sleep Mode)	2.0secs. or less	
Print Language	UFR II LT	
Print Margin	5mm-top, bottom, left and right (Other sizes than Envelope) 10mm-top, bottom, left and right (Envelope)	
<b>COPY</b>		
Copy Speed (A4)	23ppm	
Copy Resolution	600 x 600dpi	
First Copy Time (FCOT) A4	Approx. 9.0secs.	
Maximum Number of Copies	Up to 999 copies	
Reduce / Enlargement	25 - 400% in 1% increments	
Copy Features	Memory Sort, 2 on 1, 4 on 1, ID Card Copy	
<b>SCAN</b>		
Scan Type	Colour Contact Image Sensor	
Scan Resolution	Optical	Up to 600 x 600dpi
	Driver Enhanced	Up to 9,600 x 9,600dpi
Maximum Scan Size	Platen Glass	Up to 216 x 297mm
Scan Speed	Platen Glass	Approx. 3.0secs. per sheet (mono) Approx. 4.0secs. per sheet (colour)
Colour Depth	24-bit	
Pull Scan	Yes, USB and Network	
Push Scan (Scan To PC) with MF	Yes, USB and Network	
Scan To Cloud	Yes, MF Scan Utility	
Scan Driver Compatibility	TWAIN, WIA, ICA	
<b>PAPER HANDLING</b>		
Paper Input	Standard Cassette	250 sheets
	Multi-Purpose Tray	1 sheet
Paper Output (Based on 68g/m <sup>2</sup> )	100 sheets (face down)	
Paper Size	Standard Cassette	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom (Min. 76.2 x 210mm)

1/10/20

		to Max. 216 x 356mm)
	Multi-Purpose Tray	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom (Min. 76.2 x 127mm to Max. 216 x 356mm)
Paper Type		Plain, Heavy, Recycled, Colour, Bond, Label, Index Card, Envelope
<b>CONNECTIVITY &amp; SOFTWARE</b>		
Standard Interface	Wired	High-Speed USB 2.0 10 / 100 Base-T Ethernet
Network Interface	Print	LPD, RAW, IPP / IPPS, WSD-Print (IPv4, IPv6)
	Scan	WSD-Scan (IPv4, IPv6)
Compatible Operating Systems		Microsoft® Windows® 10 (32 / 64-bit), Windows® 8.1 (32 / 64-bit), Windows® 8 (32 / 64-bit), Windows® 7 (32 / 64-bit), Windows Vista®
Software Included		Printer driver, Scanner driver, MF Scan Utility, SSID Tool, Toner Status
<b>GENERAL</b>		
Device Memory		256MB
Operational Panel		5-line BW LCD
Dimensions (W x D x H)		390 x 371 x 312mm (Cassette closed) 390 x 441 x 312mm (Cassette opened)
Power Consumption		Maximum 1,120W or less
	During Operation (Avg.)	Approx. 420W
	During Standby (Avg.)	Approx. 4.2W
	During Sleep (Avg.)	Approx. 1.2W (USB connection) Approx. 1.3W (Wired LAN connection)
Power Requirement		AC 220 - 240V (±10%), 50 / 60Hz (±2Hz)
Consumables	Toner (Standard)	Cartridge 337: 2,400 pages (bundled: 1,700 pages)

**07. Office Table with two side drawers**

- A. Main Table
  - a. The size of main table shall be 1370 mm (W) x 690 mm (D) x 740 mm (H).
  - b. The top should be made of 18 mm thick Pre-laminated board with 2 mm thick Doelleken/equivalent beading matching lipping.
  - c. Stiffener under structure should be (1.6mm thick) C shaped CRCA steel sheet is to be provided under the top to give additional strength.
- B. Under structure
  - a. The leg and other under structure should be made of round tubular under structure frame with footrest shall be made from MS ERW round tubes dia.25.4 mm x 1.2 mm thick.
  - b. There shall be two sets of storage unit. Left unit have two drawers and Right side unit have three drawers as shown in pictorial unit. The shell of the drawer unit shall be made of 0.8 mm thick CRCA steel sheet.
  - c. Drawer slides shall be based on friction slides of 1.2 mm thick CRCA steel sheet. It should have 6 lever brass lock. The handles of drawer are made of ABS plastic fitted under the self-surface with screw. The draw should have the single locking mechanism working on under lever.

**08. Revolving chair**

- a. Seat & Back Assembly:** The seat and back shall be made of PU foam of density 45 ± 2 Kg/m<sup>3</sup> upholstered with changeable fabric upholstery covers (as per requirement). Back Size: 480 mm. (W) X 550 mm (H) Approx. Seat Size: 480 mm (W) X 550 mm. (D) Approx.
- b. Base:** Five prongs made of black colour reinforced PU plastic with Nylon wheels and pneumatic up & down with one point locking mechanism
- C. Handle armrest:** The armrest shall be gas-assisted injection moulded from Polypropylene.
- d. Revolving & Tilt:** Chair should have a full 360° revolving mechanism with 17 deg. maximum tilt only and tilt tension adjustment facility.
- e. Height of chair:** Maximum and minimum height is approx. 930 mm and 830 mm respectively.

*Handwritten signature*

**09. Visitors Chair:**

- Feature: Should Have 100% VOC Free Powder coating.  
Should be designed for long life and easy part replacement.
- b. Specification: Width-750mm  
Depth-750mm  
Height-750mm

**10. Computer Table**

- a. Overall Size : 900x500x750 mm (L x W x H) approx
- b. Understructure : It shall be made of 18 mm thick high quality Pre-laminated. Particle boards with PVC strip edge banding of all exposed edge
- c. Key board tray : This shall be attached with the key board tray
- d. Under self- structure: It should have place to keep CPU, printer and UPS. The size of the open area for CPU should be 200 mm (W) x 400 mm (D) x 500 mm (H).
- e. Fitting : The particle board should be inter fitted with metal insert type screw fitting with one draw and outer side is being closed.

**11. Steel Alamirah**

- a. Overall size : W x H x D: 1018.5 mm x 1980 mm x 535.9 mm (3 ft 4 in x 6 ft 5 in x 1 ft 9 in)
- b. Materials : The CRCA steel sheet used for the body should be 0.9 mm thick,
- c. Construction : It should interlocking design and full length over lapping doors and sides. It should have three way bolting mechanism. The two doors have hinge mounted on frame
- d. Doors : The doors have one handle and lever locking mechanism with 6- Six lever Zinc Plated Lock.
- e. Powder coating : All steel components should undergo eight tank anti rust treatment and oven Baked epoxy polyester powder coating with 50-60 micron dry film thickness.
- f. Shelves inside Almirah with locker and without locker

**12. Voltage Stabilizer (1 /5 kv) 0.5KV**

Description	
Input Voltage	90 - 280 volt
Output Voltage	220 volt
Frequency	50 Hz
Insulation	Greater Than 6 M Ohms
Mode Of Operation	Automatic
Response Time	60 seconds
Duty Cycle	Continuous
Efficiency	Better Than 98%
Transformer	All copper wound on CRGO Lamination as per ISO specification for higher efficiency and low loss
Salient Features	Input/ Output voltage shown by voltmeter on front panel

**13. DG Set**

Description	
Fuel Type	Diesel/Petrol
Power	5KVA
Phase	Single Phase
Cooling System	Oil /Air
Fuel Tank Capacity	Minimum 15 Ltrs
Voltage	220-380 V
Warranty	Minimum Two year on site
Noise Level	50-60 HZ or silent type

16/2/2010

**14. INVERTER**

UPS Specification for 2 KVA  
2 KVA, 1680 W, Sine Wave inverter, support two batteries  
24 Month Warranty  
Safe for sensitive appliances with Sine wave out-put  
Auto over-load handling capacity  
Installation and maintenance friendly

Description : For Single Battery with 1.1 KVA Capacity	
OUT PUT Power	1.1 KVA
Voltage	12 V
Wave Form	Sine wave
Recharge Time	6 Hrs
Warranty	2 years on site

**15. BATTERY**

150 Ah capacity, 12V  
Warranty 48\* Months  
Tubular Technology battery Robust Tubular plates  
Low antimony alloy used for low maintenance  
Suitable for areas with frequent and long power cuts

**16. INVERTER BATTERY TROLLEY**

Double Battery  
Plastic  
Non Breakable

**17. RACK**

Type: Open | 10 Shelves ,Metal  
W x H x D: 85 cm x 125 cm x 26 cm (2 ft 9 in x 4 ft 1 in x 10 in)  
Mount: Free Standing  
Style: Contemporary & Modern  
DIY - Basic assembly to be done with simple tools by the customer, comes with instructions.

**18. PLASTIC CHAIR**

Material: Plastic  
Colour: Brown and Beige  
Dimensions (L x W x H): 60 cm x 60 cm x 89 cm  
Assembly: No Assembly Required  
Installation: Free Standing

**19. ORNET CHAIR**

Upholstery Included | Upholstery Type: Cushion  
Style: Contemporary & Modern  
W x H x D: 365 mm x 520 mm x 360 mm (1 ft 2 in x 1 ft 8 in x 1 ft 2 in)  
Pre Assembled (Ready to Use)

**20. Projector with Presenter**

Description	
Type	WXGA (1280 X 800)
Contast Ratio	3000:1
Aspect Ratio	16:10
Illumination	3700
Life of Lamp	7000hrs
Extra Features	Audio,USB port,HDMI Input S-video Input
Installation	Roof installation

*Handwritten signature/initials in green ink.*

Projector Screen	6 " X 6 " with stand
Warranty Type	Onsite
<b>Presenter</b>	
Compatible OS	Window 7 or Greater version of windows
Laser Class	Class 2 Laser
Battery Type	2 AAA batteries
Battery Life(Laser)	20 Hrs Max
Battery Life( Presenter)	1050 Hrs Max
Wireless Operating Distance	Approx. 10 Mtrs
Interface	USB

**21.Desk top**

Description	
Processor	2.2 GhzGHz Intel i3 8130U 8th Gen processor 7200 RPM Intel i5 9400 9th Gen processor
Ram	4GB DDR4 RAM for i3 and 8GB for i5
Graphics	2 GB or more
Memory	1TB 7200rpm hard drive
OS	Windows 10, Home operating system
Display	21.5-inch screen, Intel UHD Graphics 620 Graphics
Others	LAN,WI-FI,Bluetooth,integrated web cam,key board with palm rest,4 usb port,HDMI port,VGA port card reader,DVD RW
Warranty	Onsite 3 year

**22.SMART TV SPECIFICATION**

Display Size	125.73 cm (50)
Screen Type	LED
HD Technology & Resolution	Ultra HD (4K), 3840 x 2160
Smart TV	Yes
Series	AI Powered K31
HDMI	3
USB	2
Wi-Fi Type	2.4GHz, 802.11 b/g/n 2T2R
Built In Wi-Fi	Yes
Internet Features	
Built In Wi-Fi	Yes
Ethernet (RJ45)	1
Other Internet Features	Android Pie 9 ,Google Assistant,Voice Search,Google Play Store Chromecast Built-in ,Netflix,YouTube
Headphone Jack	Yes
Other Connectivity Features	Ethernet Port, 3 HDMI, 2 USB, SPDIF, Bluetooth
Smart Tv Features	
Number of Cores	4
Processor	Amlogic 64bit A55x4 900MHz~1.1GHz
Graphic Processor	Mali470x3 600MHz-800MHz
Ram Capacity	2 GB
Storage Memory	16 GB
Supported Mobile Operating System	Android iOS
Audio Features	
Number of Speakers	2
Speaker Type	Box Speakers

*Handwritten signature and date*  
22/2/20

Sound Technology  
 Surround Sound  
 Speaker Output RMS  
 Sound Mode  
 Supported Audio Formats  
 Other Audio Features

Dolby Audio MS 12  
 Yes  
 20 W  
 Dynamic, Standard, Movie, Music, Voice, Game, Stadium  
 MP3, WMA, AAC, AC3, AC4  
 AI Sound Engine, Dolby Audio MS 12, Sound Modes, Equalizers -  
 Dynamic/Standard/Movie/Music/Voice/Game/Stadium

Power Features  
 Power Requirement  
 Other Power Features  
 Warranty  
 Warranty Summary

AC 100 - 240 V, 50/60 Hz  
 Instant Power ON, ECO Energy Efficiency  
 1 Year Warranty on Product

**23.CCTV**

Sales Package  
 Number of Channels  
 Camera Type  
 Video Output  
 Video Recording Resolution  
 Video Recording Frame Rate  
 Product Details

6 Bullet Camera & DVR with All Accessorie Complete CCTV Combo Set  
 8  
 BNC  
 HDMI, VGA  
 1080p/720p  
 30fps

Number of IR LEDs  
 HDD Available  
 HDD Type  
 HDD Size  
 Power And Connectivity Features

12  
 Yes  
 SATA  
 3.5 inch

Network Interface Type

RJ45

Number of USB Ports

3

USB Type

2

Number of Ethernet Ports

1

Audio Interface

4 Audio

Additional Features

Material

Metal

Model Name

2.4MP 6 Bullet Camera & DVR with All UPVsales® Accessories Complete CCTV Combo Set

Color

Multicolor

Lens Size

3.6 mm

Angle of View

120 degree

Warranty

Warranty Summary

Camera & DVR Have 2 Year Warranty, Hard Disk Have 3 Year Warranty, Power Supply Have 1 Year Warranty

**24.WEBCAM**

Basic requirements: 1 GHz 512 MB RAM or more 200 MB hard drive space Internet connection USB 1.1 port (2.0 recommended) For HD 720p video calling and HD recording: 2.4 GHz Intel® Core™2 Duo 2 GB RAM 200 MB hard drive space USB 2.0 port 1 Mbps upload speed or higher 1280 x 720 screen resolution Warranty Information 2-Year Limited Hardware Warranty Package Contents Webcam with 5-foot cable Technical Specifications The specs: HD Video calling (1280 X 720 pixels) with recommended system HD video capture: Up to 1280 X 720 pixels

**25.SOFA**

25	Sofa	Depth 30 inch, Seat Height 18 Inch, Total Height 30 Inch) Stainless Steel legs Wooden frame ( Mirandi Wood) PU Foam Seat Leatherette Uphostlery
----	------	---

Handwritten signature or mark

**Specification of Printing Material**

SI No	Name of the Item	*Specification
26	Patient referral cards at PHC Level	<p><b>Unit: Booklet</b>                      No. of Sheets: 50 (50 sheets marked as Original + 50 sheets marked as Duplicate) with One carbon sheet in each booklet.                      Printing Type (Inner Sheets): <u>Single side</u>, Black                      1<sup>st</sup> Sheet of the Booklet shall be printed as "Original" and the next sheet shall be printed as "Duplicate" (for taking carbon copy) and this will be <u>repeated</u> in the remaining sheets of the booklet.                      Paper Size : ¼ Demy                      Paper : Original Sheet ( White Colour)- 80 GSM Maplitho, Brightness " 80 (Minimum)                      Duplicate Sheet ( Yellow Colour) – 54 GSM Maplitho                      Binding Type : Top Pad binding with stapling with ½ pound hard board on back side Cover Page : 1 cover page on the front ( 80 GSM maplitho Single side Black Printing as Patient Referral Card-PHC)                      Perforation: Perforation at the of the Pad Binding ( in Original sheet of the booklet only)</p>
27	Patient referral cards at Sub Centre Level	<p><b>Unit : Booklet</b>                      No. of Sheets: 50 (50 Sheets marked as original + 50 sheets Marked as Duplicate) with One carbon sheet in each booklet.                      Printing Type (Inner sheets) : <u>Single side</u>, Black                      It Sheet of the Booklet shall be printed as : " Original" and the next sheet shall be printed as " Duplicate" ( for taking carbon copy) and will be <u>repeated</u> in the remaining sheets of the booklet.                      Paper Size : ¼ Demy                      Paper : Original Sheet (White Colour) – 80 GSM Maplitho, Brightness : 80 (Minimum)                      Duplicate Sheet ( Yellow Colour) – 54 GSM Maplitho                      Binding Type : Top pad binding with stapling with ½ pound hard board on back side Cover Page: 1 cover page on the front (80 GSM Maplitho Single sided Black Printing as " Patient Referral Card – Sub Center"                      Perforation: Perforation at the of the Pad Binding(In Original sheet of the booklet)</p>
28	Flip Book	<p><b>Unit : Flip Book</b>                      Size : 12" x 8"                      Total no. of Flip Sheets : 15 Sheets                      Paper ( Flip Sheets): 300 GSM Art Paper ( Gloss Finish), Brightness : 80 (Minimum)                      Printing ( Flip Sheet) : Multi – Colour both side offset printing                      Lamination : Both side Lamination of the flip sheets                      Binding : Wiro Top binding with 20 mm Wiro                      Flip Stand Cover : Flip Stand cover (1 ½ Pound Mill board: 2 Nos connected with each other with base having folding arrangement for hand held as well as table top postion) having white Art paper [ 130 GSM, Brightness : 80 (min.)] pasting with Wiro binding</p>
29	NCD Drugs Paper Pouch	<p><b>Unit : Envelop</b>                      Size : 4.5" x 9"                      Paper : 90 GSM Maplitho Paper, Brightness : 77 ( Minimum)                      Printing : Single Colour Printing (IEC message with Logo)</p>
30		<p><b>Unit : Booklet</b>                      Size : ¼ Demy</p>

*Handwritten signature/initials*

	Case Record & Information Sheet NTCP	Total No. of Pages : 12 <u>Paper</u> 8 Pages : 80 GSM Maplitho Paper, Brightness : 77( Minimum 4 Pages : 90 GSM Maplitho Paper, Brightness : 77( Minimum <u>Printing</u> 8 Pages : Both side Single Colour Printing 4 Pages : single side Multicolour Printing Binding : Centre Stitching Perforation : Perforation at middle of 9 <sup>th</sup> page and side with border at 11 <sup>th</sup> page ( in 90 GSM Maplitho paper).
31	Handouts - Teacher/ Anganwadi (3 Fold)	Job type: Folder design, colour, front + back, CMYK (4 colour) Orientation: landscape Print process: Offset Printing Paper type: 100 GSM Final print size: 16.54" x 23.39" inches (Custom size) Post processes: Creasing Double Perforation
32	Flipcharts - Teacher/Anganwadi	Job type: Flipchart, colour, front + back, CMYK (4 colour) Orientation: Portrait; Wall calendar style. Refer to image Print process: Offset Paper type: 170gsm - 220 GSM, uncoated Final print size: 16.54" x 23.39" inches (A2) Post processes: Spiral binding Cardboard on the back Metal eye (rivet) for hanging it from a nail Front & Back mirror printing; 1-3, 2-5, 4-7, 6-9, 8-11, 10-13 .... 20-blank
33	ASHA Leaflet	Job type: Colour, front + back, CMYK (4 colour) Orientation: Portrait Print process: Offset Printing Paper type: 100 GSM uncoated Final print size: 8.27" x 11.69" inches (A4) Post processes: None
34	Posters (Date and Positive Behavior)	Job type: Colour, one-sided, CMYK (4 colour) Orientation: Portrait Print process: Offset Printing Paper type: 100-140 GSM, uncoated Final print size: 16.54" x 23.39" inches (A2) Post processes: None
35	Banner	Job type: Colour, one-sided, CMYK (4 colour) Orientation: Landscape Print process: Offset Printing Material: Flex Final print size: 4 feet x 2 feet Post processes: None
36	Hoarding	Job type: Colour, one-sided, CMYK (4 colour) Orientation: Landscape Print process: Offset Printing Material: Flex Final print size: 12 feet x 10 feet Post processes: None
37	Handbill (2 Variations)	Job type: Colour, front + back, CMYK (4 colour) Orientation: Portrait Print process: Offset Printing Paper type: 100-140 GSM, uncoated Final print size: 8.27" x 11.69" (A4) Post processes: None
38	Mini Checklist.	Job type: Colour, front + back, CMYK (4 colour) Orientation: Portrait Print process: Offset Printing Paper type: 100 gsm, uncoated Final print size: 8.27" x 11.69" (A4) Post processes: None

*Handwritten signature/initials in green ink.*